

Product Specifications

Style Number	VV735
Construction	Waterproof Foamed Core
Edge Profile	Pressed Bevel
Nominal Dimensions	7" wide, 60" long

	US Units	Metric Units
Actual Product Width	7.05"	18 cm
Actual Product Length	59.84"	152 cm
Wear Layer Thickness	20 mil (0.02")	0.5 mm
Overall Product Thickness	0.295"	7.5 mm
Core Thickness	0.197"	5 mm
Attached Underlayment	Attached Cork	
Attached Underlayment Thickness	0.039"	1 mm
Finish	UV Acrylic	
Installation Methods	Floating or Direct Glue	
Profile	Angle/Tap	
Country of Origin	Imported	

Packaging

Area per Box	23.43 sq ft	2 sq m
Pieces per Box	8 pcs	
Weight per Box	36.68 lbs	16.63 kg
Boxes per Pallet	65 boxes	



3018 Tyro Walnut

Colors



CT HD 7X60 INTG

Performance

Static Load (ASTM F970)	Passes
Residual Indentation (ASTM F1914)	Passes
Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Smoke Density (ASTM E662)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
Slip Resistance (ASTM D2047)	ADA compliant

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

USF Lifetime Limited


[Residential Resilient Limited Warranty - Defects, Wear, Waterproof, Petproof](#)

USF 10 Year Medium Commercial

Certifications


GreenGuard (Certification, Gold, Private Label) Certified

Coordinating Trim




Baby Threshold*

BT7CT | 94"




T-Molding*

TM7CT | 94"



Quarter Round

QTRCT | 94"



Flush Stairnose

FS7HU | 94"

*Packaged with molding track

Stair Tread



Stair Tread

03Z70 | 48"

